

Spendor Audio, May 2021

Garantie 5 ans, Prix in CHF, TVA inclue, product and price changes reserved, replaces all previous price lists

A line

A1	2-way stand mounted speaker; sealed enclosure (pair)	1490
A2	2-way floor standing loudspeaker; Spendor bass reflex enclosure (pair)	2190
A4	2-way floor standing loudspeaker; Spendor bass reflex enclosure (pair)	3090
A7	2-way floor standing loudspeaker; Spendor linear flow port enclosure (pair)	4190
A1C	2-way center speaker; sealed enclosure (piece)	990
A1W	2-way on-wall stereo/surround speaker; sealed enclosure (pair)	1890

Finishes: oak, walnut, black, white

Grills included

D line

D7.2	2.5-way floor standing loudspeaker; Spendor linear flow port enclosure (pair)	5990
D9.2	3-way floor standing loudspeaker; Spendor linear flow port enclosure (pair)	10290

Finishes: oak, walnut, cherry, black, white

Grills included

Classic line

Classic 4/5	2-way stand mounted speaker; sealed enclosure (pair)	1990
Classic 3/1	2-way stand mounted speaker; reflex enclosure (pair)	3490
Classic 2/3	2-way stand mounted speaker; reflex enclosure (pair)	4790
Classic 1/2	3-way stand mounted speaker; reflex enclosure (pair)	7490
Classic 100	3-way stand mounted speaker; reflex enclosure; new kevlar enforced papercone woofers (pair)	11490
Classic 100Ti	As above, but special version with titanium sandwich front baffle, corpus natural walnut	12990
Classic 200	3-way floor standing loudspeaker; Spendor sealed enclosure; new kevlar enforced papercone woofers (pair)	21990
Classic 200Ti	As above, but special version with titanium sandwich front baffle, corpus natural walnut	24990

Finishes: walnut, cherry

Grills included

Stands for Classic line

NEW: Stand Classic 2/3	Dedicated stand for Classic 2/3, brushed stainless steel (pair)	1290
NEW: Stand Classic 1/2	Dedicated stand for Classic 1/2, brushed stainless steel (pair)	1490
NEW: Stand Classic 100	Dedicated stand for Classic 100, brushed stainless steel (pair)	1690

Finish: black

Antispikes

Set of 8	AntiSpikes combine the advantages of hard coupling with regulated damping. Combining the two methods results an optimal energy transfer from the coupled component, which gives a tight and well structured low end and liberated and open mids and highs. They are suitable for all ground surfaces and allow easy movement of the loudspeaker, whilst protecting the support ground surface. Each AntiSpike can support over 100 kg. They have a diameter of 28mm, a height of 20mm and are supplied with M8 thread.	120
----------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----